



★ FASTENERS

Military-Fasteners.com

P/N MS20822-8D

Description

tube outer diameter: 1/2", tube thread: 3/4-16, pipe thread: 3/8", flared pipe to tube, aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208228D
Minimum Qty (MOQ):	2
NSN:	4730-00-287-1024
ECCN:	9A991
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS20822-8D Specifications

Thread Class:	3a 1st End
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	1.219 Inches Minimum 2nd End And 1.266 Inches Maximum 2nd End
Leg Length:	1.250 Inches Minimum 1st End And 1.297 Inches Maximum 1st End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Nominal Thread Size:	0.375 Inches 2nd End
Nominal Thread Size:	0.750 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.500 Inches 1st End
Special Features:	Grumman A-10 Aircraft
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/4 Temper T6 Fed Spec Single Material Response Overall Or Qq-a-225/6 Temper T6 Or T851 Fed Spec Single Material Response Overall Or Qq-a-367 Temper T6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Thread Series Designator:	Anpt 2nd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	96906-ms20822 Government Standard

How to Order

Order this pipe to tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-8D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.