

P/N MS20823-4

Description

tube outer dia: 1/4", tube thread: 7/16-20, pipe thread: 1/8", 37 degree, flared pipe to tube, carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

AS5196-0402

SKU / Model: MS208234

Minimum Qty (MOQ):

NSN: 4730-00-231-3960

ECCN: EAR99

National Motor Freight: 052190, Pipe, tubing, or Pipe Or Tubing Fitti









P/N MS20823-4 Specifications

Nominal Pipe Size Accommodated:	0.125 Inches 2nd End
Thread Class:	3a 1st End
Maximum Operating Temp:	225.0 Deg Fahrenheit Single Response
End Item Identification:	Aircraft Application
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	0.625 Inches Nominal 2nd End
Leg Length:	0.703 Inches Nominal 1st End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.125 Inches 2nd End
Nominal Thread Size:	0.438 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	45.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.250 Inches 1st End
Material:	Steel Comp 1137 Overall Or Steel Comp 1141 Overall
Material Document And Classification:	66,aisi/sae C1137 Or C1141 Fed Std Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Npt 2nd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	96906-ms20823 Government Standard

How to Order

Order this pipe to tube elbow from our inventory online by visiting https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20823-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.