

Description

tube outer diameter: 5/16", tube thread: 1/2-20, pipe thread: 1/8", flared pipe to tube, aluminum alloy, MS20823 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208235D
Minimum Qty (MOQ):	1
NSN:	4730-00-186-9980
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



P/N MS20823-5D Specifications

Thread Class:	3a 1st End
End Item Identification:	F-18 Aircraft Application
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	0.625 Inches Nominal 2nd End
Leg Length:	0.750 Inches Nominal 1st End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.125 Inches 2nd End
Nominal Thread Size:	0.500 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	45.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.312 Inches 1st End
Special Features:	Grumman Aerospace A-10 Aircraft
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-225/0,2014,temper6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Npt 2nd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	96906-ms20823 Government Standard

How to Order

Order this pipe to tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20823-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.