

Description

tube outer diameter: 3/8", tube thread: 9/16-18, pipe thread: 1/4", flared pipe to tube, corrosion resistant steel, MS20823 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208236J
Minimum Qty (MOQ):	1
NSN:	4730-00-813-7405
Schedule B:	7307.22.5000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS20823-6J Specifications

Thread Class:	3a 1st End
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	0.812 Inches Nominal 1st End
Leg Length:	0.844 Inches Nominal 2nd End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Nominal Thread Size:	0.250 Inches 2nd End
Nominal Thread Size:	0.562 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	45.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.375 Inches 1st End
Material:	Steel Comp 304 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Npt 2nd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	96906-ms20823 Government Standard

How to Order

Order this pipe to tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20823-6J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.