

P/N MS20825-3D

Description

tube outer dia: 3/16", tube thread: 3/8-24, pipe thread: 1/8", aluminum alloy - pipe to tube - pipe thread on side "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208253D
Minimum Qty (MOQ):	1
NSN:	4730-00-279-0458
National Motor Freight:	051400, Pipe Fittings Aluminum



^{*} See page 2 for technical characteristics

P/N MS20825-3D Specifications

Thread Class:	3a 2nd End
Thread Class:	3a 1st End
Connection Style:	Flared (tube) 1st End
Connection Style:	Flared (tube) 2nd End
Connection Style:	Plain (pipe) 3rd End
Leg Length:	0.688 Inches Nominal 3rd End
Leg Length:	0.797 Inches Nominal 1st End
Connection Type:	Threaded External Pipe 3rd End
Connection Type:	Threaded External Tube 1st End
Connection Type:	Threaded External Tube 2nd End
Nominal Thread Size:	0.125 Inches 3rd End
Nominal Thread Size:	0.375 Inches 2nd End
Nominal Thread Size:	0.375 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Seat Angle:	37.0 Degrees 2nd End
Nominal Outside Diameter Tube Accommodated:	0.188 Inches 1st End
Nominal Outside Diameter Tube Accommodated:	0.188 Inches 2nd End
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Inside
Surface Treatment:	Anodize Outside
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Inside
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Outside
Thread Series Designator:	Anpt 3rd End
Thread Series Designator:	Unf 1st End
Thread Series Designator:	Unf 2nd End

How to Order

Order this pipe to tube tee from our inventory online by visiting https://military-fasteners.com/fittings/pipe+to+tube+tees/MS20825-3D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.