

P/N MS20825-4J

Description

tube outer dia: 1/4", tube thread: 7/16-20, pipe thread: 1/8" - corrosion resistant steel - pipe to tube - pipe thread on side

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS208254J

Minimum Qty (MOQ):

NSN: 4730-00-228-1076

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



^{*} See page 2 for technical characteristics

P/N MS20825-4J Specifications

Thread Class:	3a 2nd End
Thread Class:	3a 1st End
Connection Style:	Flared (tube) 1st End
Connection Style:	Flared (tube) 2nd End
Connection Style:	Plain (pipe) 3rd End
Leg Length:	0.750 Inches Minimum 3rd End And 0.797 Inches Maximum 3rd End
Leg Length:	0.859 Inches Minimum 2nd End And 0.906 Inches Maximum 2nd End
Leg Length:	0.859 Inches Minimum 1st End And 0.906 Inches Maximum 1st End
Connection Type:	Threaded External Pipe 3rd End
Connection Type:	Threaded External Tube 1st End
Connection Type:	Threaded External Tube 2nd End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.125 Inches 3rd End
Nominal Thread Size:	0.438 Inches 2nd End
Nominal Thread Size:	0.438 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Seat Angle:	37.0 Degrees 2nd End
Nominal Outside Diameter Tube Accommodated:	0.250 Inches 1st End
Nominal Outside Diameter Tube Accommodated:	0.250 Inches 2nd End
Material:	Steel Comp 304 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,type 1 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Anpt 3rd End
Thread Series Designator:	Unjf 2nd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	96906-ms20825 Government Standard

How to Order

Order this pipe to tube tee from our inventory online by visiting https://military-fasteners.com/fittings/pipe+to+tube+tees/MS20825-4 and selecting the quantity

