

Description

tube outer dia: 5/8", tube thread: 7/8-14, pipe thread: 1/2", aluminum alloy, pipe to tube, pipe thread on run

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2082610D
Minimum Qty (MOQ):	1
NSN:	4730-00-277-5052
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum

NO IMAGE
AVAILABLE

P/N MS20826-10D Specifications

Thread Class:	3a 3rd End
Thread Class:	3a 1st End
Connection Style:	Flared (tube) 1st End
Connection Style:	Flared (tube) 3rd End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	1.422 Inches Minimum 1st End And 1.469 Inches Maximum 1st End
Leg Length:	1.422 Inches Minimum 3rd End And 1.469 Inches Maximum 3rd End
Leg Length:	1.438 Inches Minimum 2nd End And 1.485 Inches Maximum 2nd End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Connection Type:	Threaded External Tube 3rd End
Nominal Thread Size:	0.500 Inches 2nd End
Nominal Thread Size:	0.875 Inches 1st End
Nominal Thread Size:	0.875 Inches 3rd End
Seat Angle:	37.0 Degrees 1st End
Seat Angle:	37.0 Degrees 3rd End
Nominal Outside Diameter Tube Accommodated:	0.625 Inches 1st End
Nominal Outside Diameter Tube Accommodated:	0.625 Inches 3rd End
Material:	Aluminum Alloy 2014 Overall
Material Document And Classification:	Qq-a-367,t6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Anpt 2nd End
Thread Series Designator:	Unjf 3rd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	96906-ms20826 Government Standard

How to Order

Order this pipe to tube tee from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+tees/MS20826-10D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.