

## **P/N MS20826-10D**

### **Description**

tube outer dia: 5/8", tube thread: 7/8-14, pipe thread: 1/2", aluminum alloy, pipe to tube, pipe thread on run

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

| SKU / Model:            | MS2082610D                     |
|-------------------------|--------------------------------|
| Minimum Qty (MOQ):      | 1                              |
| NSN:                    | 4730-00-277-5052               |
| ECCN:                   | EAR99                          |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20826-10D Specifications

| Thread Class:                                  | 3a 3rd End   |
|--|--|
| Thread Class:                                  | 3a 1st End   |
| Connection Style:                              | Flared (tube) 1st End  |
| Connection Style:                              | Flared (tube) 3rd End  |
| Connection Style:                              | Plain (pipe) 2nd End   |
| Leg Length:                                    | 1.422 Inches Minimum 1st End And 1.469 Inches Maximum 1st End        |
| Leg Length:                                    | 1.422 Inches Minimum 3rd End And 1.469 Inches Maximum 3rd End        |
| Leg Length:                                    | 1.438 Inches Minimum 2nd End And 1.485 Inches Maximum 2nd End        |
| Connection Type:                               | Threaded External Pipe 2nd End                                       |
| Connection Type:                               | Threaded External Tube 1st End                                       |
| Connection Type:                               | Threaded External Tube 3rd End                                       |
| Nominal Thread Size:                           | 0.500 Inches 2nd End   |
| Nominal Thread Size:                           | 0.875 Inches 1st End   |
| Nominal Thread Size:                           | 0.875 Inches 3rd End   |
| Seat Angle:                                    | 37.0 Degrees 1st End   |
| Seat Angle:                                    | 37.0 Degrees 3rd End   |
| Nominal Outside Diameter Tube Accommodated:    | 0.625 Inches 1st End   |
| Nominal Outside Diameter Tube Accommodated:    | 0.625 Inches 3rd End   |
| Material:                                      | Aluminum Alloy 2014 Overall  |
| Material Document And Classification:          | Qq-a-367,t6 Fed Spec Single Material Response Overall                |
| Surface Treatment:                             | Anodize Overall  |
| Surface Treatment Document And Classification: | Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall |
| Thread Series Designator:                      | Anpt 2nd End   |
| Thread Series Designator:                      | Unjf 3rd End   |
| Thread Series Designator:                      | Unjf 1st End   |
| Specification/standard Data:                   | 96906-ms20826 Government Standard                                    |
|  |  |

## **How to Order**

Order this pipe to tube tee from our inventory online by visiting <a href="https://military-fasteners.com/fittings/pipe+to+tube+tees/MS20826-10D">https://military-fasteners.com/fittings/pipe+to+tube+tees/MS20826-10D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.