

P/N MS20826-3D

Description

tube outer dia: 3/16", tube thread: 3/8-24, pipe thread: 1/8", aluminum alloy - pipe to tube, pipe thread on run

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS208263D
Minimum Qty (MOQ):	1
NSN:	4730-00-277-5043
National Motor Freight:	051400, Pipe Fittings Aluminum



^{*} See page 2 for technical characteristics

P/N MS20826-3D Specifications

3a 3rd End
3a 1st End
Flared (tube) 1st End
Flared (tube) 3rd End
Plain (pipe) 2nd End
0.688 Inches Minimum 2nd End And 0.735 Inches Maximum 2nd End
0.797 Inches Minimum 1st End And 0.844 Inches Maximum 1st End
0.797 Inches Minimum 3rd End And 0.844 Inches Maximum 3rd End
Threaded External Pipe 2nd End
Threaded External Tube 1st End
Threaded External Tube 3rd End
3000.0 Pounds Per Square Inch Single Response
0.125 Inches 2nd End
0.375 Inches 1st End
0.375 Inches 3rd End
37.0 Degrees 1st End
37.0 Degrees 3rd End
0.188 Inches 1st End
0.188 Inches 3rd End
Aluminum Alloy 2014 Overall
Qq-a-367,t6 Fed Spec Single Material Response Overall
Fluid Single Response
Anodize Overall
Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
Anpt 2nd End
Unjf 3rd End
Unjf 1st End
96906-ms20826 Government Standard

How to Order

