

## P/N MS20826-4D

## **Description**

tube outer diameter: 1/4", tube thread: 7/16-20, pipe thread: 1/8", aluminum alloy, pipe to tube, MS20826 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

## AN826-4D

SKU / Model: MS208264D

Minimum Qty (MOQ):

NSN: 4730-00-278-5126

ECCN: EAR99

National Motor Freight: 051400, Pipe Fittings Aluminum









# P/N MS20826-4D Specifications

| Thread Class:                                  | 3a 3rd End  |
|--|---|
| Thread Class:                                  | 3a 1st End  |
| Maximum Operating Temp:                        | -65.0 Deg Fahrenheit 2nd Response   |
| Maximum Operating Temp:                        | 225.0 Deg Fahrenheit 1st Response   |
| Connection Style:                              | Flared (tube) 1st End   |
| Connection Style:                              | Flared (tube) 3rd End   |
| Connection Style:                              | Plain (pipe) 2nd End  |
| Leg Length:                                    | 0.742 Inches Minimum 2nd End And 0.758 Inches Maximum 2nd End   |
| Leg Length:                                    | 0.848 Inches Minimum 1st End And 0.866 Inches Maximum 1st End   |
| Leg Length:                                    | 0.848 Inches Minimum 3rd End And 0.866 Inches Maximum 3rd End   |
| Connection Type:                               | Threaded External Pipe 2nd End  |
| Connection Type:                               | Threaded External Tube 1st End  |
| Connection Type:                               | Threaded External Tube 3rd End  |
| Maximum Operating Pressure:                    | 3000.0 Pounds Per Square Inch Single Response   |
| Nominal Thread Size:                           | 0.125 Inches 2nd End  |
| Nominal Thread Size:                           | 0.438 Inches 3rd End  |
| Nominal Thread Size:                           | 0.438 Inches 1st End  |
| Seat Angle:                                    | 37.0 Degrees 1st End  |
| Seat Angle:                                    | 37.0 Degrees 3rd End  |
| Nominal Outside Diameter Tube Accommodated:    | 0.250 Inches 1st End  |
| Nominal Outside Diameter Tube Accommodated:    | 0.250 Inches 3rd End  |
| Special Features:                              | End Item: Grumman A10 Aircraft  |
| Material:                                      | Aluminum Alloy 2014 Overall Or Aluminum Alloy 7075 Overall  |
| Material Document And Classification:          | Qq-a-367,t6 Fed Spec 1st Material Response Overall Or Qq-a-367,t73 Fed Spec 2nd Material Response Overall |
| Media For Which Designed:                      | Hydraulic Fluid 1st Response  |
| Media For Which Designed:                      | Oxygen, Gaseous 2nd Response  |
| Surface Treatment:                             | Anodize Overall   |
| Surface Treatment Document And Classification: | Mil-a-8625,type 2,class Mil Spec Single Treatment Response Overall  |
| Thread Series Designator:                      | Anpt 2nd End  |
| Thread Series Designator:                      | Unjf 3rd End  |
| Thread Series Designator:                      | Unjf 1st End  |

# **How to Order**

Order this pipe to tube tee from our inventory online by visiting <a href="https://military-fasteners.com/fittings/pipe+to+tube+tees/MS20826-4D">https://military-fasteners.com/fittings/pipe+to+tube+tees/MS20826-4D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.