

Description

Wire diameter: 0.032, 1LB roll, corrosion resistant steel, uncoated, MS20995 series wire, approx 365 feet long

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS20995-C32](#)

SKU / Model:	MS20995C32
Minimum Qty (MOQ):	1
NSN:	9505-00-293-4208
Schedule B:	8544.49.3080
ECCN:	EAR99
National Motor Freight:	107480, Wire / Barbed Wire I / S Acid Coppered



* See page 2 for technical characteristics

P/N MS20995C32 Specifications

Length:	365.000 Feet Nominal
Cross Section Outside Diameter:	0.032 Inches Nominal
End Item Identification:	Mrap Rg-33 Auv
lii End Item Identification:	Mrap Rg-33 Auv; Mrap Buffalo Mk2a2
Basic Shape Style:	Round
Weight Per Unit Measure:	1.000 Pounds Per Piece
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Heat Treatment:	Annealed
Material:	Steel, Astm A580, Comp 302
Material:	Steel Comp 302
Material Document And Classification:	Astm A580, Comp 302 Assn Std Single Material Response
Surface Treatment:	Passivate
Surface Treatment:	Passivated
Nondefinitive Spec/std Data:	302 Type And A Condition

How to Order

Order this safety wire from our inventory online by visiting <https://military-fasteners.com/shop+supplies/safety+wires/MS20995C32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.