

**Description**

Wire diameter: 0.032, 1LB roll, corrosion resistant steel, uncoated, MS20995 series wire, approx 365 feet long

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[MS20995-C32](#)

SKU / Model:	MS20995C32
Minimum Qty (MOQ):	1
NSN:	9505-00-293-4208
Schedule B:	8544.49.3080
ECCN:	EAR99
National Motor Freight:	107480, Wire / Barbed Wire I / S Acid Coppered



\* See page 2 for technical characteristics

## P/N MS20995C32 Specifications

<b>Length:</b>	365.000 Feet Nominal
<b>Cross Section Outside Diameter:</b>	0.032 Inches Nominal
<b>End Item Identification:</b>	Mrap Rg-33 Auv
<b>iii End Item Identification:</b>	Mrap Rg-33 Auv; Mrap Buffalo Mk2a2
<b>Basic Shape Style:</b>	Round
<b>Weight Per Unit Measure:</b>	1.000 Pounds Per Piece
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Heat Treatment:</b>	Annealed
<b>Material:</b>	Steel, Astm A580, Comp 302
<b>Material:</b>	Steel Comp 302
<b>Material Document And Classification:</b>	Astm A580, Comp 302 Assn Std Single Material Response
<b>Surface Treatment:</b>	Passivate
<b>Surface Treatment:</b>	Passivated
<b>Nondefinitive Spec/std Data:</b>	302 Type And A Condition

## How to Order

Order this safety wire from our inventory online by visiting <https://military-fasteners.com/shop+supplies/safety+wires/MS20995C32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.