

Description

Wire diameter: 0.032, 1LB roll, corrosion resistant steel, uncoated, MS20995 series wire, approx 365 feet long

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS20995-C32](#)

| | |
|-------------------------|--|
| SKU / Model: | MS20995C32 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 9505-00-293-4208 |
| Schedule B: | 8544.49.3080 |
| ECCN: | EAR99 |
| National Motor Freight: | 107480, Wire / Barbed Wire I / S Acid Coppered |



* See page 2 for technical characteristics

P/N MS20995C32 Specifications

| | |
|--|---|
| Length: | 365.000 Feet Nominal |
| Cross Section Outside Diameter: | 0.032 Inches Nominal |
| End Item Identification: | Mrap Rg-33 Auv |
| iii End Item Identification: | Mrap Rg-33 Auv; Mrap Buffalo Mk2a2 |
| Basic Shape Style: | Round |
| Weight Per Unit Measure: | 1.000 Pounds Per Piece |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Heat Treatment: | Annealed |
| Material: | Steel, Astm A580, Comp 302 |
| Material: | Steel Comp 302 |
| Material Document And Classification: | Astm A580, Comp 302 Assn Std Single Material Response |
| Surface Treatment: | Passivate |
| Surface Treatment: | Passivated |
| Nondefinitive Spec/std Data: | 302 Type And A Condition |

How to Order

Order this safety wire from our inventory online by visiting <https://military-fasteners.com/shop+supplies/safety+wires/MS20995C32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.