

Description

Thread: 6-32, reduced hexagon, reduced height, cad plated steel, dry film lubricated, MS21042 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[BACN10FX61](#)

| | |
|-------------------------|---|
| SKU / Model: | MS21042L06 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-00-807-1472 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS21042L06 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.244 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.115 Inches Minimum And 0.141 Inches Maximum |
| Nut Style: | Hexagon |
| Washer Thickness: | 0.010 Inches Minimum |
| Width Across Flats: | 0.181 Inches Minimum And 0.190 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjc |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.138 Inches |
| Criticality Code Justification: | Feat |
| Special Features: | Nut Self-locking |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS21042L06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.