

P/N MS21042L4

Description

Thread: 1/4-28, 450 degree, reduced hexagon, reduced height, cad plated steel, dry film lubricated, MS21042 series nut

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS21042L4

Minimum Qty (MOQ): 25

NSN: 5310-00-807-1475

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS21042L4 Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.420 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.204 Inches Minimum And 0.219 Inches Maximum |
| Nut Style: | Hexagon |
| Washer Thickness: | 0.019 Inches Minimum |
| Width Across Flats: | 0.304 Inches Minimum And 0.316 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 28 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.250 Inches |
| Criticality Code Justification: | Feat |
| Special Features: | Weapons System Essential |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS21042L4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.