

## P/N MS21042L5

### **Description**

Thread: 5/16-24, reduced hexagon, reduced height, cad plated steel, dry film lubricated. locknut, MS21042 series nut

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21042L5

Minimum Qty (MOQ): 25

NSN: 5310-00-807-1476

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# **P/N MS21042L5 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.520 Inches Maximum
Lubrication:	Dry Film Lubricant
Overall Height:	0.251 Inches Minimum And 0.266 Inches Maximum
Nut Style:	Hexagon
Washer Thickness:	0.023 Inches Minimum
Width Across Flats:	0.367 Inches Minimum And 0.378 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this self-locking extended washer nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/MS21042L5">https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/MS21042L5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.