

Description

Thread: 3/8-24, reduced hexagon, reduced height, cad plated steel, dry film lubricated, MS21042 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21042L6 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-00-807-1477 |
| Schedule B: | 7318.16.0030 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21042L6 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.620 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.267 Inches Minimum And 0.282 Inches Maximum |
| Nut Style: | Hexagon |
| Washer Thickness: | 0.030 Inches Minimum |
| Width Across Flats: | 0.430 Inches Minimum And 0.440 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.375 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 26512-gn10u Manufacturers Standard |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS21042L6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.