

**Description**

Thread: 4-40, locking nut, reduced hexagon, reduced height, silver plated, corrosion and heat resistant steel, MS21043 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1DAX86A044082](#) [PLH504](#)

SKU / Model:	MS2104304
Minimum Qty (MOQ):	50
NSN:	5310-00-878-3292
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS21043-04 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Washer Outside Diameter:</b>	0.206 Inches Maximum
<b>Lubrication:</b>	Soluble Lubricant
<b>Overall Height:</b>	0.103 Inches Minimum And 0.125 Inches Maximum
<b>Nut Style:</b>	Hexagon
<b>Washer Thickness:</b>	0.010 Inches Minimum
<b>Width Across Flats:</b>	0.150 Inches Minimum And 0.158 Inches Maximum
<b>Temp Rating:</b>	800.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjc
<b>Thread Quantity Per Inch:</b>	40
<b>Nominal Thread Size:</b>	0.112 Inches
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall
<b>Precious Material And Location:</b>	Overall Silver
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Overall
<b>Surface Treatment Document And Classification:</b>	Qq-s-365 Fed Spec Single Treatment Response Overall Or Ams 2410 Assn Std Single Treatment Response Overall

## How to Order

Order this self-locking extended washer nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+extended+washer+nuts/MS21043-04](https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS21043-04) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.