

P/N MS21043-04

Description

Thread: 4-40, locking nut, reduced hexagon, reduced height, silver plated, corrosion and heat resistant steel, MS21043 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

1DAX86A044082 PLH504

SKU / Model: MS2104304

Minimum Qty (MOQ): 50

NSN: 5310-00-878-3292

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N MS21043-04 Specifications

| Thread Class: | 3b |
|--|--|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.206 Inches Maximum |
| Lubrication: | Soluble Lubricant |
| Overall Height: | 0.103 Inches Minimum And 0.125 Inches Maximum |
| Nut Style: | Hexagon |
| Washer Thickness: | 0.010 Inches Minimum |
| Width Across Flats: | 0.150 Inches Minimum And 0.158 Inches Maximum |
| Temp Rating: | 800.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjc |
| Thread Quantity Per Inch: | 40 |
| Nominal Thread Size: | 0.112 Inches |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall |
| Precious Material And Location: | Overall Silver |
| Precious Material: | Silver |
| Surface Treatment: | Silver Overall |
| Surface Treatment Document And Classification: | Qq-s-365 Fed Spec Single Treatment Response Overall Or Ams 2410 Assn Std Single Treatment Response Overall |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS21043-04 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.