

Description

Thread: 3/8-24, self locking, regular height, corrosion resistant steel, nylon insert, passivated, MS21044 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21044C6](#)

SKU / Model:	MS21044C6
Minimum Qty (MOQ):	25
NSN:	5310-00-857-4959
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21044-C6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.318 Inches Minimum And 0.469 Inches Maximum
End Item Identification:	Rg-33 Auv Mrap
Width Across Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Special Features:	.
Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Nut
Material Document And Classification:	Ams 5688 Assn Std 1st Material Response Or Ams 5630 Assn Std 2nd Material Response Or Ams 5647 Assn Std 3rd Material Response Nut
Surface Treatment:	Passivate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21044-C6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.