

## P/N MS21044B06

## **Description**

Thread Size: 1/8", Nut Height: 1/8", Head Width: 1/4", MS21044 series nut

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS21044B06

Minimum Qty (MOQ): 25

NSN: 5310-00-877-5622

Schedule B: 7415.33.8050

ECCN: EAR99

National Motor Freight: 093460, Bolts / Nuts Noi Bbc / Zinc







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21044B06 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.160 Inches Minimum And 0.188 Inches Maximum
Width Across Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Copper Alloy 360 Nut Or Copper Alloy 260 Nut
Surface Treatment:	Cadmium Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Except Insert

## **How to Order**

Order this locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/MS21044B06">https://military-fasteners.com/nuts/locknuts/MS21044B06</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/locknuts/MS21044B06">https://military-fasteners.com/nuts/locknuts/MS21044B06</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/locknuts/MS21044B06">https://military-fasteners.com/nuts/locknuts/MS21044B06</a> and selecting the quantity you want then click "add to cart".