

**Description**

Thread Size: 1/8", Nut Height: 1/4", Head Width: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                     |
|-------------------------|-------------------------------------|
| SKU / Model:            | MS21044B08                          |
| Minimum Qty (MOQ):      | 10                                  |
| NSN:                    | 5310-00-982-5063                    |
| Schedule B:             | 7415.33.8050                        |
| ECCN:                   | EAR99                               |
| National Motor Freight: | 093460, Bolts / Nuts Noi Bbc / Zinc |



## P/N MS21044B08 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3b  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Locking Feature:</b>                               | Prevailing Torque With Nonmetallic Insert                                   |
| <b>Lubrication:</b>                                   | Soluble Lubricant   |
| <b>Nut Style:</b>                                     | Hexagon   |
| <b>Nut Height:</b>                                    | 0.219 Inches Minimum And 0.281 Inches Maximum                               |
| <b>Width Across Flats:</b>                            | 0.336 Inches Minimum And 0.345 Inches Maximum                               |
| <b>Temp Rating:</b>                                   | 250.0 Deg Fahrenheit Nominal  |
| <b>Thread Series:</b>                                 | Unjc  |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Nominal Thread Size:</b>                           | 0.164 Inches  |
| <b>Countersink Angle:</b>                             | 88.0 Degrees Nominal Nut  |
| <b>Bearing Surface Type:</b>                          | Chamfered Or Washer Faced   |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches   |
| <b>Material:</b>                                      | Copper Alloy 360 Nut Or Copper Alloy 260 Nut                                |
| <b>Surface Treatment:</b>                             | Cadmium Overall Except Insert   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Except Insert |

## How to Order

Order this self-locking hexagon nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+hexagon+nuts/MS21044B08](https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21044B08) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.