

**Description**

Thread Size: 3/4", Nut Height: 7/8", locknut, nylon insert, fine thread, soluble lubricant, MS21044 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[79NE126](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS21044C12                                |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5310-00-267-9974                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS21044C12 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3b  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Locking Feature:</b>                               | Prevailing Torque With Nonmetallic Insert   |
| <b>Lubrication:</b>                                   | Soluble Lubricant   |
| <b>Nut Style:</b>                                     | Hexagon   |
| <b>Nut Height:</b>                                    | 0.855 Inches Minimum And 0.891 Inches Maximum   |
| <b>End Item Identification:</b>                       | Rg-33 Auv Mrap  |
| <b>Width Across Flats:</b>                            | 1.052 Inches Minimum And 1.064 Inches Maximum   |
| <b>Temp Rating:</b>                                   | 250.0 Deg Fahrenheit Nominal  |
| <b>Thread Series:</b>                                 | Unjf  |
| <b>Thread Quantity Per Inch:</b>                      | 16  |
| <b>Nominal Thread Size:</b>                           | 0.750 Inches  |
| <b>Countersink Angle:</b>                             | 88.0 Degrees Nominal Nut  |
| <b>Bearing Surface Type:</b>                          | Chamfered Or Washer Faced   |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches   |
| <b>Material:</b>                                      | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Nut  |
| <b>Material Document And Classification:</b>          | Ams 5688 Assn Std 1st Material Response Or Ams 5640 Assn Std 2nd Material Response Or Ams 5647 Assn Std 3rd Material Response Nut |
| <b>Surface Treatment:</b>                             | Passivate Overall Except Insert   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert  |

## How to Order

Order this self-locking hexagon nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+hexagon+nuts/MS21044C12](https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21044C12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.