

P/N MS21044C12

Military-Fasteners.com

Description

Thread Size: 3/4", Nut Height: 7/8", locknut, nylon insert, fine thread, soluble lubricant, MS21044 series nut

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

<u>79NE126</u>	
SKU / Model:	MS21044C12
Minimum Qty (MOQ):	1
NSN:	5310-00-267-9974
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)





* See page 2 for technical characteristics

P/N MS21044C12 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.855 Inches Minimum And 0.891 Inches Maximum
End Item Identification:	Rg-33 Auv Mrap
Width Across Flats:	1.052 Inches Minimum And 1.064 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	16
Nominal Thread Size:	0.750 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Nut
Material Document And Classification:	Ams 5688 Assn Std 1st Material Response Or Ams 5640 Assn Std 2nd Material Response Or Ams 5647 Assn Std 3rd Material Response Nut
Surface Treatment:	Passivate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21044C12</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.