

Description

thread: 7/16-20, self locking, regular height, nylon insert, corrosion resistant steel, passivated, MS21044 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21044C7 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-00-225-6190 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21044C7 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Lubrication: | Soluble Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.435 Inches Minimum And 0.469 Inches Maximum |
| Width Across Flats: | 0.679 Inches Minimum And 0.690 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.438 Inches |
| Countersink Angle: | 88.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Steel Comp 302 Nut Or Steel Comp 303 Nut Or Steel Comp 304 Nut |
| Material Document And Classification: | Ams 5688 Assn Std 1st Material Response Nut Or Ams 5640 Assn Std 2nd Material Response Nut Or Ams 5647 Assn Std 3rd Material Response Nut |
| Surface Treatment: | Passivate Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21044C7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.