

P/N MS21044D08

Description

thread: 8-32, self locking, regular height, aluminum alloy, nylon insert, anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NMJ832

SKU / Model: MS21044D08

Minimum Qty (MOQ): 25

NSN: 5310-00-060-2039

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS21044D08 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.219 Inches Minimum And 0.281 Inches Maximum
Width Across Flats:	0.336 Inches Minimum And 0.345 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Aluminum Alloy 2014 Nut Or Aluminum Alloy 2017 Nut Or Aluminum Alloy 2024 Nut Or Aluminum Alloy 7075 Nut
Material Document And Classification:	Qq-a-200/2,t6 Fed Spec 1st Material Response Nut Or Qq-a-225/5,t4 Fed Spec 2nd Material Response Nut Or Qq-a-225/6,t6 Fed Spec 3rd Material Response Nut Or Qq-a-200/11,t6 Fed Spec 4th Material Response Nut
Surface Treatment:	Anodize Overall Except Insert Or Chromate Overall Except Insert
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21044D08 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.