

**Description**

Thread Size: 5/8", Nut Height: 3/4", Head Width: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21044D10
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-982-6803
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

## P/N MS21044D10 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque With Nonmetallic Insert
<b>Lubrication:</b>	Soluble Lubricant
<b>Nut Style:</b>	Hexagon
<b>Nut Height:</b>	0.732 Inches Minimum And 0.766 Inches Maximum
<b>Width Across Flats:</b>	0.928 Inches Minimum And 0.940 Inches Maximum
<b>Temp Rating:</b>	250.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	18
<b>Nominal Thread Size:</b>	0.625 Inches
<b>Countersink Angle:</b>	88.0 Degrees Nominal Nut
<b>Bearing Surface Type:</b>	Chamfered Or Washer Faced
<b>Bearing Surface Finish:</b>	125.0 Microinches
<b>Material:</b>	Aluminum Alloy Overall Or Plastic Polyamide Overall

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21044D10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.