

Description

Thread Size: 5/8", Nut Height: 3/4", Head Width: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21044D10
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-982-6803
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N MS21044D10 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.732 Inches Minimum And 0.766 Inches Maximum
Width Across Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	18
Nominal Thread Size:	0.625 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Aluminum Alloy Overall Or Plastic Polyamide Overall

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21044D10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.