

## P/N MS21044D3

### **Description**

thread: 10-32, self locking, regular height, aluminum alloy, nylon insert, anodized

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21044D3

Minimum Qty (MOQ): 25

NSN: 5310-00-877-5798

ECCN: EAR99

National Motor Freight: 013540, Alum Nuts









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21044D3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.208 Inches Minimum And 0.281 Inches Maximum
Width Across Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Aluminum Locking Insert
Material:	Plastic Polyamide Overall Except Insert
Surface Treatment:	Anodize Overall Except Insert And Chromate Overall Except Insert
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Except Insert And Mil-c-5541 Mil Spec 2nd Treatment Response Overall Except Insert

## **How to Order**

Order this self-locking hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21044D3">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21044D3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.