

**Description**

Thread Size: 1", Nut Height: 1-1/8", Head Width: 1-3/8",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21044N16
Minimum Qty (MOQ):	5
NSN:	5310-00-057-7151
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS21044N16 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque With Nonmetallic Insert
<b>Counterbore Diameter:</b>	1.024 Inches Minimum Nut And 1.064 Inches Maximum Nut
<b>Lubrication:</b>	Soluble Lubricant
<b>Nut Style:</b>	Hexagon
<b>Nut Height:</b>	1.010 Inches Minimum And 1.141 Inches Maximum
<b>Width Across Flats:</b>	1.427 Inches Minimum And 1.440 Inches Maximum
<b>Temp Rating:</b>	250.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	12
<b>Nominal Thread Size:</b>	1.000 Inches
<b>Countersink Angle:</b>	88.0 Degrees Nominal Nut
<b>Bearing Surface Type:</b>	Chamfered Or Washer Faced
<b>Bearing Surface Finish:</b>	125.0 Microinches
<b>Material:</b>	Steel Comp 1006 Nut Or Steel Comp 1008 Nut Or Steel Comp 1009 Nut Or Steel Comp 1010 Nut Or Steel Comp 1015 Nut Or Steel Comp 1018 Nut Or Steel Comp 1035 Nut Or Steel Comp 11137 Nut Or Steel Comp 1213 Nut Or Steel Comp 12114 Nut
<b>Surface Treatment:</b>	Cadmium Nut And Chromate Nut
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Nut

## How to Order

Order this self-locking hexagon nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+hexagon+nuts/MS21044N16](https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21044N16) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.