

P/N MS21044N9

Military-Fasteners.com

Description

thread: 9/16-18, self locking, regular height, cadmium plated steel, nylon insert, locknut, MS21044 series nut

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | MS21044N9 |
|-------------------------|---|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-982-6808 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21044N9 Specifications

| Thread Class: | 3b |
|---|--|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Lubrication: | Soluble Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.623 Inches Minimum And 0.704 Inches Maximum |
| Width Across Flats: | 0.865 Inches Minimum And 0.877 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 18 |
| Nominal Thread Size: | 0.562 Inches |
| Countersink Angle: | 88.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Steel Comp 1006 Nut Or Steel Comp 1008 Nut Or Steel Comp 1009 Nut Or Steel Comp 1010 Nut Or Steel Comp 1015 Nut Or Steel Comp 1018 Nut Or Steel Comp 1213 Nut Or Steel Comp 1214 Nut |
| Surface Treatment: | Cadmium Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Except Insert |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21044N9</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.