

## P/N MS21045-06E

### **Description**

Thread Size: 1/8", Nut Height: 1/8", Head Width: 1/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2104506E

Minimum Qty (MOQ): 25

NSN: 5310-01-506-0314

ECCN: EAR99







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21045-06E Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Nut Style:	Hexagon
Nut Height:	0.160 Inches Minimum And 0.188 Inches Maximum
Width Across Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Bearing Surface Type:	Chamfered Or Washer Faced
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

# **How to Order**

Order this self-locking hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21045-06E">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21045-06E</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21045-06E">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21045-06E</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21045-06E">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21045-06E</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+hexagon">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21045-06E</a> and selecting the property of the propert