

## Description

Thread: 5/8-18, Nut Height: 3/4", Head Width: 7/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

#### [MS21045-C10](#)

SKU / Model:	MS21045C10
Minimum Qty (MOQ):	1
NSN:	5310-00-051-8627
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS21045C10 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.636 Inches Minimum Nut And 0.676 Inches Maximum Nut
<b>Lubrication:</b>	Dry Film Lubricant
<b>Nut Style:</b>	Hexagon
<b>Nut Height:</b>	0.732 Inches Minimum And 0.766 Inches Maximum
<b>Width Across Flats:</b>	0.928 Inches Minimum And 0.940 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	18
<b>Nominal Thread Size:</b>	0.625 Inches
<b>Countersink Angle:</b>	88.0 Degrees Nominal Nut
<b>Bearing Surface Type:</b>	Chamfered Or Washer Faced
<b>Bearing Surface Finish:</b>	125.0 Microinches
<b>Material:</b>	Steel Corrosion Resisting Overall

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21045C10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.