

**Description**

Thread Size: 1", Nut Height: 1-1/8", Head Width: 1-3/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS21045C16                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5310-01-034-8889                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS21045C16 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Locking Feature:</b>                               | Prevailing Torque All Metal Design                 |
| <b>Lubrication:</b>                                   | Dry Film Lubricant                                 |
| <b>Nut Style:</b>                                     | Hexagon  |
| <b>Nut Height:</b>                                    | 1.010 Inches Minimum And 1.141 Inches Maximum      |
| <b>Width Across Flats:</b>                            | 1.427 Inches Minimum And 1.440 Inches Maximum      |
| <b>Temp Rating:</b>                                   | 450.0 Deg Fahrenheit Nominal                       |
| <b>Thread Series:</b>                                 | Unjf   |
| <b>Thread Quantity Per Inch:</b>                      | 12   |
| <b>Nominal Thread Size:</b>                           | 1.000 Inches                                       |
| <b>Countersink Angle:</b>                             | 88.0 Degrees Nominal Nut                           |
| <b>Bearing Surface Type:</b>                          | Chamfered  |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches                                  |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall                  |
| <b>Surface Treatment:</b>                             | Passivate Overall                                  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall |

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21045C16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.