

Description

thread: 1/4-28, self locking, regular height, corrosion resistant steel, with dry film lube, MS21045 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21045-C4](#)

| | |
|-------------------------|---|
| SKU / Model: | MS21045C4 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-00-982-4988 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS21045C4 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Counterbore Diameter: | 0.253 Inches Minimum Nut And 0.293 Inches Maximum Nut |
| Lubrication: | Dry Film Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.240 Inches Minimum And 0.328 Inches Maximum |
| Width Across Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Countersink Angle: | 88.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Steel Corrosion Resisting Overall |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21045C4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.