

**Description**

thread: 3/8-24, self locking, regular height, corrosion resistant steel, with dry film lube, locknut, MS21045 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | MS21045C6                                 |
| Minimum Qty (MOQ):      | 10                                        |
| NSN:                    | 5310-00-059-9264                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS21045C6 Specifications

|                                                       |                                                    |
|-------------------------------------------------------|----------------------------------------------------|
| <b>Thread Class:</b>                                  | 3b                                                 |
| <b>Thread Direction:</b>                              | Right-hand                                         |
| <b>Locking Feature:</b>                               | Prevailing Torque All Metal Design                 |
| <b>Lubrication:</b>                                   | Dry Film Lubricant                                 |
| <b>Nut Style:</b>                                     | Hexagon                                            |
| <b>Nut Height:</b>                                    | 0.318 Inches Minimum And 0.469 Inches Maximum      |
| <b>Width Across Flats:</b>                            | 0.553 Inches Minimum And 0.564 Inches Maximum      |
| <b>Temp Rating:</b>                                   | 450.0 Deg Fahrenheit Nominal                       |
| <b>Thread Series:</b>                                 | Unjf                                               |
| <b>Thread Quantity Per Inch:</b>                      | 24                                                 |
| <b>Nominal Thread Size:</b>                           | 0.375 Inches                                       |
| <b>Countersink Angle:</b>                             | 88.0 Degrees Nominal Nut                           |
| <b>Bearing Surface Type:</b>                          | Chamfered Or Washer Faced                          |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches                                  |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall                  |
| <b>Surface Treatment:</b>                             | Passivate Overall                                  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall |

## How to Order

Order this self-locking hexagon nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+hexagon+nuts/MS21045C6](https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21045C6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.