

P/N MS21045C6

Description

thread: 3/8-24, self locking, regular height, corrosion resistant steel, with dry film lube, locknut, MS21045 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS21045C6

Minimum Qty (MOQ): 10

NSN: 5310-00-059-9264

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)











^{*} See page 2 for technical characteristics

P/N MS21045C6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Nut Style:	Hexagon
Nut Height:	0.318 Inches Minimum And 0.469 Inches Maximum
Width Across Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21045C6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhttps://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21045C6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhttps://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21045C6 and selecting the quantity you want then click "add to cart".