

P/N MS21045L12

Military-Fasteners.com

Description

Thread Size: 3/4", Nut Height: 57/64", Head Width: 1-3/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS21045L12 |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5310-00-857-5975 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21045L12 Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.855 Nominal Mils And 0.891 Nominal Centimeters |
| Width Across Flats: | 1.052 Inches Minimum And 1.064 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 16 |
| Nominal Thread Size: | 0.750 Inches |
| Countersink Angle: | 88.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |

How to Order

Order this locknut from our inventory online by visiting <u>https://military-fasteners.com/nuts/locknuts/MS21045L12</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.