

Description

Thread Size: 1-1/8", Nut Height: 1-17/64", Head Width: 1-39/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21045L18
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-211-3431



\* See page 2 for technical characteristics

## P/N MS21045L18 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant Or Soluble Lubricant
<b>Nut Style:</b>	Hexagon
<b>Nut Height:</b>	1.266 Inches Maximum
<b>Width Across Flats:</b>	1.614 Inches Minimum And 1.627 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	12
<b>Nominal Thread Size:</b>	1.125 Inches
<b>Countersink Angle:</b>	120.0 Degrees Nominal Nut
<b>Bearing Surface Type:</b>	Chamfered Or Washer Faced
<b>Bearing Surface Finish:</b>	125.0 Microinches
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1021 Professional/industrial Association Standard

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21045L18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.