

Description

Thread: 5/16-24, self locking, regular height, steel nut, cadmium plated, with dry film lube, MS21045 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21045L5 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-00-857-5559 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |



P/N MS21045L5 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.271 Nominal Mils And 0.360 Nominal Centimeters |
| Width Across Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.312 Inches |
| Countersink Angle: | 88.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21045L5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.