

P/N MS21045L9

Description

Thread Size: 35/64", Nut Height: 21/32", Head Width: 55/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS21045L9

Minimum Qty (MOQ): 5

NSN: 5310-00-857-5565

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21045L9 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Nut Style:	Hexagon
Nut Height:	0.623 Nominal Mils And 0.704 Nominal Centimeters
Width Across Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	18
Nominal Thread Size:	0.562 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/locknuts/MS21045L9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.