

Description

MS21048 series nut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS210484
Minimum Qty (MOQ):	20
NSN:	5310-00-771-7349
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21048-4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.0254 Inches Minimum Nut
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.260 Inches Maximum
Nut Height:	0.281 Inches Maximum
Plate Thickness:	0.055 Inches Maximum
Plate Width:	0.375 Inches Minimum And 0.414 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	28
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Precious Material And Location:	All Surfaces Silver
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21048-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.