

P/N MS21048-5

Description

MS21048 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210485
Minimum Qty (MOQ):	5
NSN:	5310-00-771-7350
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21048-5 Specifications

Thread Direction: Right-hand Locking Feature: Prevailing Torque All Metal Design Counterbore Diameter: 0.317 Inches Minimum Nut Mounting Hole Diameter: 0.130 Inches Minimum Ad 0.135 Inches Maximum Nut Style: Plate Nut Length: 1.792 Inches Maximum Nut Height: 0.328 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.065 Inches Maximum Nut Counterbore Depth: 0.065 Inches Maximum Nut Counterbore Depth: 0.065 Inches Minimum And 0.505 Inches Maximum Nut Gountrip Provision: Straight Holes Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: Center Distance Between Mounting Hole Bols Along Length: 30,998 Inches Minimum And 0.505 Inches Maximum Center: Unif Thread Series: 0.998 Inches Minimum And 1.002 Inches Maximum Thread Series: 0.916 Thread Quantity Per Inch: 49.0 Rockwell C Maximum Material: 10 Inches Stating: 49.0 Rockwell C Maximum Material Document And Classification: Arms 5525 Asan Std Single Material Response Overall Or Ams 5732 Asan Std Single Material Response Overall Precious Material: Silver Precious Material: Silver Overall Surface Treatment Document And Classification: Silver Overall Surface Treatment Pocument And Classification: Silver Overall	Thursd Class.	a k
Locking Feature: Prevailing Torque All Metal Design Counterbore Diameter: 0.317 Inches Minimum Nut Mounting Hole Diameter: 0.320 Inches Minimum And 0.135 Inches Maximum Nut Style: Plate Nut Length: 0.328 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.655 Inches Maximum Plate Wildt: 0.485 Inches Minimum And 0.505 Inches Maximum Nut Counterbore Depth: 0.622 Inches Minimum Nut Nut Mounting Provision: 5 Fraight Holes Mounting Hole Arrangement Style: 4 Holes Distance From Aperture Center To Mounting Holes Along Length: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Tempa Asting: 800.0 Deg Fahrenheit Maximum Thread Quantity Per Inch: 4 Hardness Rating: 9.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material Document And Classification: 3.312 Inches Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall	Thread Class:	3b
Counterbore Diameter: 0.131 Inches Minimum Nut Mounting Hole Diameter: 0.130 Inches Minimum And 0.135 Inches Maximum Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Wildth: 0.065 Inches Maximum Plate Wildth: 0.405 Inches Minimum And 0.505 Inches Maximum Nut Counterbore Depth: 0.622 Inches Minimum Nut Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center TO Mounting Holes Along Length: 3.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 3.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Maximum Thread Series: Unjf Thread Series: 49.0 Rockwell C Maximum Nominal Thread Size: 49.0 Rockwell C Maximum Nominal Thread Size: 10.312 Inches Material: Iron Alloy 660 Overall Material: Iron Alloy 660 Overall Precious Material And Location: Along Actaes Silver Sizer Assans Std Single		
Mounting Hole Diameter: 0.130 Inches Minimum And 0.135 Inches Maximum Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.065 Inches Maximum Plate Width: 0.485 Inches Minimum And 0.505 Inches Maximum Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 0.002 Inches Maximum Temp Rating: 0.00 Deg Fahrenheit Maximum Thread Series: Unjf Thread Quantity Per Inch: 24 Hardness Rating: 9.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Overall	Locking Feature:	Prevailing Torque All Metal Design
Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.65 Inches Maximum Plate Width: 0.485 Inches Minimum And 0.505 Inches Maximum Nut Counterbore Depth: 0.62 Inches Minimum Nut Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 2.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Maximum Thread Series: Unjf Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material: Iron Alloy 660 Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Overall Sulface Treatment: Silver Overall	Counterbore Diameter:	0.317 Inches Minimum Nut
Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.065 Inches Maximum Plate Width: 0.485 Inches Minimum And 0.505 Inches Maximum Nut Counterbore Depth: 0.061 Inches Minimum Nut Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Maximum Thread Series: Unjf Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: 10.312 Inches Material Document And Classification: 3.373 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Brecious Material: Silver Overall	Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Height: 0.328 Inches Maximum Plate Thickness: 0.065 Inches Maximum Plate Width: 0.485 Inches Minimum And 0.505 Inches Maximum Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Maximum Thread Series: Unjf Thread Quantity Per Inch: 49.0 Rockwell C Maximum Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material Document And Classification: 737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Surface Treatment: Silver Overall	Nut Style:	Plate
Plate Thickness: 0.065 Inches Maximum Plate Width: 0.485 Inches Minimum And 0.505 Inches Maximum Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 0.998 Inches Minimum And 1.002 Inches Maximum Thread Series: Unjf Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 5737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Overall	Nut Length:	1.292 Inches Maximum
Plate Width: 0.485 Inches Minimum And 0.505 Inches Maximum Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Maximum Thread Series: Unjf Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Surface Treatment: Silver Overall	Nut Height:	0.328 Inches Maximum
Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Bloes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Maximum Thread Series: Unjf Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Surface Treatment: Silver Overall	Plate Thickness:	0.065 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:800.0 Deg Fahrenheit MaximumThread Series:UnjfThread Quantity Per Inch:24Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.312 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallPrecious Material And Location:All Surfaces SilverPrecious Material:Silver OverallSurface Treatment:Silver Overall	Plate Width:	0.485 Inches Minimum And 0.505 Inches Maximum
Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Maximum Thread Series: Unjf Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Surface Treatment: Silver Overall	Nut Counterbore Depth:	0.062 Inches Minimum Nut
Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Maximum Thread Series: Unjf Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Surface Treatment: Silver Overall	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length: Temp Rating: No.998 Inches Minimum And 1.002 Inches Maximum Thread Series: Unjf Thread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: All Surfaces Silver Precious Material: Silver Overall Silver Overall	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Maximum Thread Series: Unjf Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Surface Treatment: Silver Overall	•	0.495 Inches Minimum And 0.505 Inches Maximum
Thread Series: Unjf Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Silver Silver Overall	_	0.998 Inches Minimum And 1.002 Inches Maximum
Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Overall	Temp Rating:	800.0 Deg Fahrenheit Maximum
Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Surface Treatment: Silver Overall	Thread Series:	Unjf
Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material And Location: All Surfaces Silver Precious Material: Silver Overall	Thread Quantity Per Inch:	24
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallPrecious Material And Location:All Surfaces SilverPrecious Material:SilverSurface Treatment:Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material And Location: Precious Material: Silver Surface Treatment: Silver Overall	Nominal Thread Size:	0.312 Inches
Precious Material And Location: Precious Material And Location: Precious Material: Silver Surface Treatment: Silver Overall	Material:	Iron Alloy 660 Overall
Precious Material: Silver Surface Treatment: Silver Overall	Material Document And Classification:	
Surface Treatment: Silver Overall	Precious Material And Location:	All Surfaces Silver
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

