

Description

Thread: 6-32, two lug, corrosion resistant, MS21048 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21048L06K
Minimum Qty (MOQ):	10
NSN:	5310-01-191-1432
Schedule B:	7318.16.0085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N MS21048L06K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Any Acceptable
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Nut Height:	0.171 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.239 Inches Minimum And 0.265 Inches Maximum
Nut Mounting Provision:	Countersunk Holes Or Dimpled Holes
Mounting Provision Location:	Opposite Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.138 Inches
Mounting Hole Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
Special Features:	Dry Film Lubricant
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5525 Assn Std Single Material Response Overall Or Ams5735 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment Document And Classification:	Mil-n-25027 Mil Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21048L06K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.