

## P/N MS21050-3

## **Description**

thread: 10-32, self-locking, two lug, side by side, reduced rivet spacing, low height, corrosion resistant steel, silver plated, plain rivet holes

\* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

## R2100C3

SKU / Model: MS210503

Minimum Qty (MOQ): 10

NSN: 5310-00-782-0011

ECCN: FAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21050-3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
	Prevailing Torque All Metal Design
Locking Feature:	
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Nut Height:	0.281 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.406 Inches Minimum And 0.453 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Countersink Angle:	99.0 Degrees Minimum Nut And 101.0 Degrees Maximum Nut
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

# **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self-locking+nutplates/MS21050-3">https://military-fasteners.com/nuts/self-locking+nutplates/MS21050-3</a> and selecting the

