

Description

thread: 6-32, self-locking, one lug low height, cadmium plated carbon steel, with dry film lube, countersunk rivet holes, MS21051 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21051L06K
Minimum Qty (MOQ):	20
NSN:	5310-00-784-1215
Schedule B:	7318.16.0030
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21051L06K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.935 Inches Maximum
Nut Height:	0.171 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.239 Inches Minimum And 0.297 Inches Maximum
Nut Mounting Provision:	Countersunk Holes
Mounting Provision Location:	Opposite Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.138 Inches
Mounting Hole Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21051L06K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.