

Description

Thread Size: 3/16", Nut Length: 1", Nut Height: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21052L3 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-00-732-0711 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS21052L3 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.950 Inches Maximum |
| Nut Height: | 0.250 Inches Maximum |
| Plate Thickness: | 0.047 Inches Maximum |
| Plate Width: | 0.308 Inches Minimum And 0.328 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.339 Inches Minimum And 0.349 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.310 Inches Minimum And 0.314 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21052L3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.