

## P/N MS21055-3

## **Description**

10-32 thread, self-locking corner nutplate, low height, cadmium plated carbon steel, without dry film lube, plain rivet holes

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS210553

Minimum Qty (MOQ): 25

NSN: 5310-00-779-3513

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21055-3 Specifications

| Thread Class:  | 3b  |
|--|---|
| Thread Direction:                                      | Right-hand  |
| Locking Feature:                                       | Prevailing Torque All Metal Design                          |
| Counterbore Diameter:                                  | 0.062 Inches Minimum Nut                                    |
| Lubrication:   | Soluble Lubricant   |
| Mounting Hole Diameter:                                | 0.098 Inches Minimum And 0.103 Inches Maximum               |
| Nut Style:   | Plate   |
| Nut Length:  | 0.653 Inches Maximum  |
| Nut Height:  | 0.250 Inches Maximum  |
| Plate Thickness:                                       | 0.047 Inches Maximum  |
| Nut Counterbore Depth:                                 | 0.194 Inches Minimum Nut                                    |
| Nut Mounting Provision:                                | Straight Holes  |
| Mounting Hole Arrangement Style:                       | 2 Holes   |
| Distance From Aperture Center To Mounting Hole Center: | 0.339 Inches Minimum And 0.349 Inches Maximum               |
| Temp Rating:   | 450.0 Deg Fahrenheit Maximum                                |
| Thread Series:   | Unjf  |
| Thread Quantity Per Inch:                              | 32  |
| Hardness Rating:                                       | 49.0 Rockwell C Maximum                                     |
| Nominal Thread Size:                                   | 0.190 Inches  |
| Material:  | Steel Overall   |
| Surface Treatment:                                     | Cadmium Overall And Chromate Overall                        |
| Surface Treatment Document And Classification:         | Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall |

### **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21055-3">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21055-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21055-3">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21055-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21055-3">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21055-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21055-3">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21055-3</a> and selecting the quantity you want then click "add to cart".