

## P/N MS21060-08

### **Description**

thread: 8-32, self locking two lug, floating, low height, corrosion resistant steel, silver plated, plain rivet holes, MS21060 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

#### 10AX86A087N84

SKU / Model: MS2106008

Minimum Qty (MOQ): 20

NSN: 5310-00-780-1046

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21060-08 Specifications

Thread Direction: Right-hand Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.948 Inches Maximum Nut Height: 0.948 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.290 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: Center: 0.339 Inches Minimum And 0.349 Inches Maximum Center: 0.339 Inches Minimum And 0.690 Inches Maximum Holes Along Length: 800.0 Deg Fahrenheit Nominal Thread Series: Unjc Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.164 Inches Material: 100cument And Classification: Ams 5735 Asan Std Single Material Response Overall Or Ams 5737 Asan Std Single Material Response Overall Precious Material: Silver Overall	Thread Class:	3b
Locking Feature:         Prevailing Torque All Metal Design           Mounting Hole Diameter:         0.098 Inches Minimum And 0.103 Inches Maximum           Nut Style:         Plate           Nut Length:         0.948 Inches Maximum           Nut Height:         0.250 Inches Maximum           Plate Thickness:         0.032 Inches Maximum           Plate Wildth:         0.290 Inches Minimum And 0.416 Inches Maximum           Nut Mounting Provision:         5 traight Holes           Mut Mounting Hole Arrangement Style:         2 Holes           Distance From Aperture Center To Mounting Hole         0.339 Inches Minimum And 0.349 Inches Maximum           Center:         0.686 Inches Minimum And 0.690 Inches Maximum           Center Distance Between Mounting Holes Along Length:         0.686 Inches Minimum And 0.690 Inches Maximum           Tomas Along Length:         0.00 Deg Fahrenheit Nominal           Temp Rating:         0.00 Deg Fahrenheit Nominal           Thread Series:         Unjc           Features Provided:         Floating Nut           Thread Quantity Per Inch:         32           Hardness Rating:         49.0 Rockwell C Maximum           Nominal Thread Size:         49.1 Rockwell C Maximum           Material Document And Classification:         5555 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Sin		
Mounting Hole Diameter:         0.98 Inches Minimum And 0.103 Inches Maximum           Nut Style:         Plate           Nut Length:         0.948 Inches Maximum           Nut Height:         0.250 Inches Maximum           Plate Thickness:         0.032 Inches Maximum           Plate Width:         0.290 Inches Minimum And 0.416 Inches Maximum           Nut Mounting Provision:         Straight Holes           Mounting Hole Arrangement Style:         2 Holes           Distance From Aperture Center To Mounting Hole Center:         0.339 Inches Minimum And 0.349 Inches Maximum           Center To Center Distance Between Mounting Holes Along Length:         0.686 Inches Minimum And 0.690 Inches Maximum           Moles Along Length:         800.0 Deg Fahrenheit Nominal           Temp Rating:         800.0 Deg Fahrenheit Nominal           Thread Series:         10 July           Features Provided:         10 Jet Inches           Thread Quantity Per Inch:         32           Hardness Rating:         9.0 Rockwell C Maximum           Nominal Thread Size:         0.164 Inches           Material:         Iron Alloy 660 Overall           Material Document And Classification:         Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall           Precious Material:         Silver Overall<		
Nut Style: Nut Length: O.948 Inches Maximum Nut Height: O.250 Inches Maximum Plate Thickness: O.32 Inches Maximum Plate Thickness: O.32 Inches Maximum Plate Width: O.290 Inches Minimum And 0.416 Inches Maximum Plate Width: Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: Boo.0 Deg Fahrenheit Nominal Thread Series: Unjo: Features Provided: Thread Quantity Per Inch: 32 Hardness Rating: Nominal Thread Size: Moninal Thread Size: Moninal Thread Size: Material: Inn Alloy 660 Overall Material: Material Document And Classification: Silver Overall  Amerial Document And Classification: Silver Overall Silver Overall		
Nut Length: Nut Height: O.250 Inches Maximum Plate Thickness: O.325 Inches Maximum Plate Width: O.290 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Provision: Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: Center Distance Between Mounting Hole Center: Center To Center Distance Between Mounting Hole Senting: Temp Rating: Temp Rating: Diojc Features Provided: Thread Series: Features Provided: Thread Quantity Per Inch: 32 Hardness Rating: Ago No Rockwell C Maximum Nominal Thread Size: Material: Iron Alloy 660 Overall Material: Silver Overall  Material Document And Classification: Silver Overall Silver Overall	_	
Nut Height: Plate Thickness: 0.032 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Nut Mounting Provision: Ustance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: 0.00.0 Deg Fahrenheit Nominal Thread Series: Unic Features Provided: Floating Nut Thread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Center Io Alloy 660 Overall Material Document And Classification: S525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Sulver Overall Sulver Overall	-	
Plate Thickness:       0.032 Inches Maximum         Plate Width:       0.290 Inches Minimum And 0.416 Inches Maximum         Nut Mounting Provision:       Straight Holes         Mounting Hole Arrangement Style:       2 Holes         Distance From Aperture Center To Mounting Hole Center:       0.339 Inches Minimum And 0.349 Inches Maximum         Center To Center Distance Between Mounting Holes Along Length:       0.686 Inches Minimum And 0.690 Inches Maximum         Temp Rating:       800.0 Deg Fahrenheit Nominal         Thread Series:       Unjc         Features Provided:       Floating Nut         Thread Quantity Per Inch:       32         Hardness Rating:       49.0 Rockwell C Maximum         Nominal Thread Size:       0.164 Inches         Material:       Iron Alloy 660 Overall         Material Document And Classification:       Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall         Precious Material:       Silver	Nut Length:	0.948 Inches Maximum
Plate Width:       0.290 Inches Minimum And 0.416 Inches Maximum         Nut Mounting Provision:       Straight Holes         Mounting Hole Arrangement Style:       2 Holes         Distance From Aperture Center To Mounting Hole Center:       0.339 Inches Minimum And 0.349 Inches Maximum         Center To Center Distance Between Mounting Holes Along Length:       0.686 Inches Minimum And 0.690 Inches Maximum         Holes Along Length:       800.0 Deg Fahrenheit Nominal         Temp Rating:       800.0 Deg Fahrenheit Nominal         Thread Series:       Unjc         Features Provided:       Floating Nut         Thread Quantity Per Inch:       32         Hardness Rating:       49.0 Rockwell C Maximum         Nominal Thread Size:       0.164 Inches         Material:       1ron Alloy 660 Overall         Material Document And Classification:       Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall         Precious Material:       Silver         Surface Treatment:       Silver Overall	Nut Height:	0.250 Inches Maximum
Nut Mounting Provision:       Straight Holes         Mounting Hole Arrangement Style:       2 Holes         Distance From Aperture Center To Mounting Hole Center:       0.339 Inches Minimum And 0.349 Inches Maximum         Center To Center Distance Between Mounting Holes Along Length:       0.686 Inches Minimum And 0.690 Inches Maximum         Temp Rating:       800.0 Deg Fahrenheit Nominal         Thread Series:       Unjc         Features Provided:       Floating Nut         Thread Quantity Per Inch:       32         Hardness Rating:       49.0 Rockwell C Maximum         Nominal Thread Size:       0.164 Inches         Material:       Iron Alloy 660 Overall         Material Document And Classification:       Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall         Precious Material:       Silver         Surface Treatment:       Silver Overall	Plate Thickness:	0.032 Inches Maximum
Mounting Hole Arrangement Style:       2 Holes         Distance From Aperture Center To Mounting Hole Center:       0.339 Inches Minimum And 0.349 Inches Maximum         Center To Center Distance Between Mounting Holes Along Length:       0.686 Inches Minimum And 0.690 Inches Maximum         Temp Rating:       800.0 Deg Fahrenheit Nominal         Thread Series:       Unjc         Features Provided:       Floating Nut         Thread Quantity Per Inch:       32         Hardness Rating:       49.0 Rockwell C Maximum         Nominal Thread Size:       0.164 Inches         Material:       Iron Alloy 660 Overall         Material Document And Classification:       Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall         Precious Material:       Silver         Surface Treatment:       Silver Overall	Plate Width:	0.290 Inches Minimum And 0.416 Inches Maximum
Distance From Aperture Center To Mounting Hole Center:  Center To Center Distance Between Mounting Holes Along Length:  Temp Rating:  Bound Deg Fahrenheit Nominal  Thread Series:  Unjc  Features Provided:  Thread Quantity Per Inch:  Hardness Rating:  Nominal Thread Size:  Material:  Iron Alloy 660 Overall  Material Document And Classification:  Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall  Precious Material:  Silver  Sulface Treatment:  Silver Overall	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length:  Temp Rating:  No.866 Inches Minimum And 0.690 Inches Maximum  800.0 Deg Fahrenheit Nominal  Thread Series:  Unjc  Features Provided:  Thread Quantity Per Inch:  Hardness Rating:  Nominal Thread Size:  Material:  Iron Alloy 660 Overall  Material Document And Classification:  Size Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall  Precious Material:  Silver  Surface Treatment:  Silver Overall	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length:  Temp Rating: 800.0 Deg Fahrenheit Nominal Unjc  Features Provided: Floating Nut  Thread Quantity Per Inch: 32  Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.164 Inches Material: Iron Alloy 660 Overall  Material Document And Classification: 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall  Precious Material: Silver Surface Treatment: Silver Overall	Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Thread Series:  Floating Nut  Thread Quantity Per Inch:  Hardness Rating:  Hardness Rating:  Nominal Thread Size:  Material:  Iron Alloy 660 Overall  Material Document And Classification:  Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall  Precious Material:  Silver  Surface Treatment:  Silver  Silver  Silver	Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Features Provided: Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum  Nominal Thread Size: 0.164 Inches  Material: Iron Alloy 660 Overall  Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall	Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Quantity Per Inch:  Hardness Rating: 49.0 Rockwell C Maximum  Nominal Thread Size: 0.164 Inches  Material: Iron Alloy 660 Overall  Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall  Precious Material: Silver  Surface Treatment: Silver Overall	Thread Series:	Unjc
Hardness Rating: 49.0 Rockwell C Maximum  Nominal Thread Size: 0.164 Inches  Material: Iron Alloy 660 Overall  Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall  Precious Material: Silver  Surface Treatment: Silver Overall	Features Provided:	Floating Nut
Nominal Thread Size:  Material:  Material:  Material Document And Classification:  Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall  Precious Material:  Silver  Silver Overall	Thread Quantity Per Inch:	32
Material:  Material Document And Classification:  Material Document And Classification:  Precious Material:  Silver  Surface Treatment:  Iron Alloy 660 Overall  Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall  Silver  Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification:  Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall  Precious Material:  Silver  Silver Overall	Nominal Thread Size:	0.164 Inches
Precious Material: Surface Treatment:  5525 Assn Std Single Material Response Overall Silver Silver Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Silver Overall	Material Document And Classification:	
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

## **How to Order**

