

P/N MS21060-08K

Military-Fasteners.com

Description

Thread Size: 5/32", Nut Length: 15/16", Nut Height: 1/4

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS2106008K
Minimum Qty (MOQ):	20
NSN:	5310-00-780-1045
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



P/N MS21060-08K Specifications

Fhread Direction: Right-hand	
Locking Feature: Prevailing Torque All Metal Design	
Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum	
Nut Style: Plate	
Nut Length: 0.948 Inches Maximum	
Nut Height: 0.250 Inches Maximum	
Plate Thickness: 0.032 Inches Maximum	
Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum	
Nut Mounting Provision: Countersunk Holes	
Mounting Provision Location: Opposite Nut Projection Side	
Mounting Hole Arrangement Style: 2 Holes	
Distance From Aperture Center To Mounting Hole 0.339 Inches Minimum And 0.349 Inches Maximum	
Center To Center Distance Between Mounting Holes Along Length:	
Femp Rating: 800.0 Deg Fahrenheit Nominal	
Thread Series: Unjc	
Features Provided: Floating Nut	
Chread Quantity Per Inch: 32	
Hardness Rating: 49.0 Rockwell C Maximum	
Nominal Thread Size: 0.164 Inches	
Mounting Hole Countersink Angle: 98.0 Degrees Minimum And 102.0 Degrees Maximum	
Material: Iron Alloy 660 Overall	
Material Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall5525 Assn Std Single Material Response Overall	r Ams
Precious Material: Silver	
Surface Treatment: Silver Overall	
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	

How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+nutplates/MS21060-08K</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.